Outdoor Wall Wpc Fluted Panel Customizable With 5mm Flute Depth And Relief Texture

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Minimum Order Quantity: 100m²
- Price: Negotiable
- Delivery Time: 10days after receive deposit
- Payment Terms: L/C,T/T,D/A,D/P,Western Union,MoneyGram

FSC、LEED、GREENGUARD

Supply Ability: 40CONTAINERS PER MONTH

China

HB-DECOR



Product Specification

- Product Name:
- Eco-Certifications:
- Length:
- Flute Depth:
- Widt:
- Thickness:
- Custom Colors:
- Texture:
- Waterproof Rating:
- Material:
- Highlight:

Wpc Fluted Panel Outdoor
FSC、LEED、GREENGUARD
2m-6m Customizable
3mm, 5mm, Etc
100mm-300mm Customizable
10mm, 12mm, 15mm, 20mm, Etc
Support Pantone/RAL Color Card Matching
Wood Grain, Matte, Glossy, Relief, Etc
Water Absorption Rate <0.5%
WPC
Outdoor Wall Wpc Fluted Panel,

Outdoor Wpc Fluted Panel, Customizable Wpc Fluted Panel



Product Description

Wpc Fluted Panel Outdoor Wpc Outdoor Wall Panel Customizable

HB-DECOR's WPC Fluted Panel Outdoor combines cutting-edge wood-plastic composite technology with sleek architectural design, offering a weatherproof, low-maintenance, and aesthetically versatile solution for modern exteriors. Why Choose HB-DECOR?

✓ Premium Durability: High-density (1.3g/cm³) WPC core with UV stabilizers and fire retardants ensures fade-free performance (5+ years) and safety (Class B1 Fire Rating).

Custom Flexibility: Available in multiple fluted depths (3-8mm), widths (100-300mm), and wood-grain finishes (RAL/Pantone color matching).

Easy Installation: Compatible with hidden clip systems or aluminum rails, reducing labor costs and enabling seamless vertical/horizontal layouts.

Eco-Conscious: FSC®-certified wood fiber and recyclable materials align with sustainable building standards.
Ideal for facades, fences, and decorative screens, HB-DECOR panels marry functionality with minimalist elegance—zero rotting, warping, or painting required.

Specification

Category	Parameter	Details
Material	Composition	60-70% Wood Fiber, 30-40% HDPE/PP/PVC, UV Stabilizers, Fire Retardants
	Density	1.2-1.4 g/cm ³
Dimensions	Length	2,000-6,000 mm (Customizable)
	Width	100-300 mm (Standard: 150mm, 200mm)
	Thickness	10mm, 12mm, 15mm, 20mm (±0.3mm Tolerance)
	Flute Depth	3mm, 5mm, 8mm (Vertical/Horizontal Grooves)
Performance	Water Absorption	<0.5% (24h Immersion)
	Thermal Expansion	0.05-0.1% per °C (30-80°C Range)
	Fire Rating	Class B1 (GB8624-2012) / UL94 V-2
	UV Resistance	≥5 Years Fade-Free (QUV Accelerated Testing)
Surface	Color Options	Wood Grain (Teak, Oak, Gray, etc.), Custom RAL/Pantone Matched
	Texture	Embossed, Smooth, Brushed
Installation	Mounting System	Hidden Clips, Aluminum Rails, or Direct Screw Fixing
	Battens Spacing	300-600 mm (Recommended for Load Capacity)
Certifications	Standards	ISO 9001, ISO 14001, CE, FSC® (Optional)
Packaging	MOQ	100 m ² (Palletized, Weatherproof Wrapping)
	Lead Time	15-30 Days (Depending on Customization)

for more products please visit us on hb-buildingmaterials.com

- ✓ **Residential Exteriors** Modern façade cladding, balcony screens, and garden fences.
- ✓ Commercial Buildings Office exteriors, retail storefronts, and hotel décor.
- ✓ Public Spaces Park pavilions, bus stops, and outdoor seating areas.
- ✓ **Privacy Solutions** Terrace dividers, poolside panels, and backyard screens.
- ✓ Architectural Accents Decorative wall features, column covers, and entrance highlights.

