

Interior Wpc Wall Panels Cladding For Fluted Wpc Room Partition

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HB-DECOR
- Certification: FSC、LEED、GREENGUARD
- Minimum Order Quantity: 100m²
- Price: Negotiable
- Delivery Time: 10days after receive deposit
- Payment Terms: L/C,T/T,D/A,D/P,Western Union,MoneyGram
- Supply Ability: 40CONTAINERS PER MONTH



Product Specification

- Product Name: Wpc Wall Panel Interior
- Thickness: 10mm , 12mm , 15mm , 20mm , Etc
- Application: Wpc Room Partition
- Width: Customizable
- Feature: Fluted Wpc
- Material: WPC
- Highlight: **Wpc Room Partition ,
Interior Wpc Wall Panels Cladding ,
Fluted Wpc Room Partition**

Product Description

Wpc Room Partition Fluted Wpc Wall Panels Cladding Wpc Wall Panel Interior

Enhance your interior spaces with our WPC Room Partition Fluted WPC Wall Panels Cladding. These high-quality WPC (Wood Plastic Composite) wall panels offer a perfect blend of durability, aesthetics, and functionality. The fluted design adds a modern and elegant touch, making them ideal for wall cladding, room partitions, and interior decoration. Moisture-resistant, eco-friendly, and easy to install, these panels provide a stylish and long-lasting solution for both residential and commercial spaces. Upgrade your interiors with the sleek and versatile appeal of WPC wall panels today!

Applications

- ✓ Living Room Feature Wall
- ✓ Bedroom Headboard Cladding
- ✓ Office Partition Walls
- ✓ Hotel & Restaurant Interiors
- ✓ Retail Store Displays
- ✓ Balcony & Terrace Wall Covering
- ✓ Bathroom Moisture-Resistant Panels
- ✓ Commercial Space Decoration

Specification

Category	Parameter	Details
Material	Composition	60-70% Wood Fiber, 30-40% HDPE/PP/PVC, UV Stabilizers, Fire Retardants
	Density	1.2-1.4 g/cm ³
Dimensions	Length	2,000-6,000 mm (Customizable)
	Width	100-300 mm (Standard: 150mm, 200mm)
	Thickness	10mm, 12mm, 15mm, 20mm (±0.3mm Tolerance)
	Flute Depth	3mm, 5mm, 8mm (Vertical/Horizontal Grooves)
Performance	Water Absorption	<0.5% (24h Immersion)
	Thermal Expansion	0.05-0.1% per °C (30-80°C Range)
	Fire Rating	Class B1 (GB8624-2012) / UL94 V-2
	UV Resistance	≥5 Years Fade-Free (QUV Accelerated Testing)
Surface	Color Options	Wood Grain (Teak, Oak, Gray, etc.), Custom RAL/Pantone Matched
	Texture	Embossed, Smooth, Brushed
Installation	Mounting System	Hidden Clips, Aluminum Rails, or Direct Screw Fixing
	Battens Spacing	300-600 mm (Recommended for Load Capacity)
Certifications	Standards	ISO 9001, ISO 14001, CE, FSC® (Optional)
Packaging	MOQ	100 m ² (Palletized, Weatherproof Wrapping)
	Lead Time	15-30 Days (Depending on Customization)

HB-DECOR
Focus On Life**HAINING HAOBO BUILDING MATERIALS CO.,LTD**

+8613586328467

info@hb-decor.comhb-buildingmaterials.com

SHANGDU YINZUO 1607, NO. 271 HANING DADAO,HAIZHOU STREET,HAINING,CHINA