

# Balcony Privacy Screens Wpc Exterior Wall Panel 100mm-300mm Width Customizable

## **Basic Information**

Place of Origin: ChinaBrand Name: HB-DECOR

• Certification: FSC、LEED、GREENGUARD

Minimum Order Quantity: 100m²Price: Negotiable

• Delivery Time: 10days after receive deposit

Payment Terms: L/C,T/T,D/A,D/P,Western Union,MoneyGram

Supply Ability: 40CONTAINERS PER MONTH



# **Product Specification**

Product Name: Wpc Exterior Wall Panel
Application: Wpc Exterior Wall Panel
Eco-Certifications: FSC LEED GREENGUARD
Widt: 100mm-300mm Customizable

Custom Colors: Support Pantone/RAL Color Card Matching
Thickness: 10mm, 12mm, 15mm, 20mm, Etc

• Flute Depth: 3mm, 5mm, Etc

Material: WPC

• Highlight: 100mm-300mm Width fluted wpc,

Exterior Wall Panel fluted wpc, Balcony Privacy Screens fluted wpc

## **Product Description**

# Wpc Exterior Wall Panel Wpc Wall Sheet Balcony Privacy Screens WPC Fluted Panel

HB's high-performance WPC panels combine durability and design for modern architectural applications. Our weatherresistant panels feature a wood-plastic composite core with ASA protective layer, offering UV stability (4000+ hours tested). low water absorption (0.02%), and Class B fire rating. The system includes solid wall sheets, adjustable privacy screens, and fluted panels, all compatible with aluminum substructures. With 12 standard RAL colors and custom options, HB's solution is ideal for balconies, facades, and privacy screens, backed by a 20-year warranty.

#### Why Professionals Choose HB-DECOR:

- ✓ Deep Profile Integrity 3-8mm flute depths maintain crisp lines season after season
- ✓ Cladding-Grade Composition 65% wood fiber reinforced with impact-modified polymers
- ✓ Weatherproof Shield Patented moisture barrier prevents warping (-30°C to 80°C stable)
- ✓ Architectural Flexibility Reversible panels for vertical/horizontal installation

#### Engineered For:

- High-traffic commercial facades
- · Coastal residence weather barriers
- · Urban retrofit projects

Complete your specification package:

Fire-rated options (Class B)

Custom lengths up to 6m

RAL-matched color system

#### **Specification**

Category	Parameter	Details
	Composition	60-70% Wood Fiber, 30-40% HDPE/PP/PVC, UV Stabilizers, Fire
		Retardants
	Density	1.2-1.4 g/cm <sup>3</sup>
Dimensions	Length	2,000-6,000 mm (Customizable)
	Width	100-300 mm (Standard: 150mm, 200mm)
	Thickness	10mm, 12mm, 15mm, 20mm (±0.3mm Tolerance)
	Flute Depth	3mm, 5mm, 8mm (Vertical/Horizontal Grooves)
Performance	Water Absorption	<0.5% (24h Immersion)
	Thermal Expansion	0.05-0.1% per °C (30-80°C Range)
	Fire Rating	Class B1 (GB8624-2012) / UL94 V-2
	UV Resistance	≥5 Years Fade-Free (QUV Accelerated Testing)
Surface	Color Options	Wood Grain (Teak, Oak, Gray, etc.), Custom RAL/Pantone Matched
	Texture	Embossed, Smooth, Brushed
Installation	Mounting System	Hidden Clips, Aluminum Rails, or Direct Screw Fixing
	Battens Spacing	300-600 mm (Recommended for Load Capacity)
Certifications	Standards	ISO 9001, ISO 14001, CE, FSC® (Optional)
Packaging	MOQ	100 m <sup>2</sup> (Palletized, Weatherproof Wrapping)
	Lead Time	15-30 Days (Depending on Customization)

# HB-DECOR HAINING HAOBO BUILDING MATERIALS CO.,LTD



+8613586328467



info@hb-decor.com



hb-buildingmaterials.com

SHANGDU YINZUO 1607, NO. 271 HANING DADAO, HAIZHOU STREET, HAINING, CHINA